

## Dixon® Boss LPS Frac Fittings

### Male with Nut



3" and 4"



6" and 8"

Size	Figure	Part #
2"	200	HUM200200CS <sup>1</sup>
	206	HUM206200CS <sup>2</sup>
3"	100	HUM100300CS <sup>1</sup>
	200	HUM200300CS <sup>1</sup>
	206	HUM206300CS <sup>2</sup>
4"	100	HUM100400CS <sup>1</sup>
	200	HUM200400CS <sup>1</sup>
	206	HUM206400CS <sup>2</sup>
6"	100	HUM100600CS <sup>1</sup>
	200	HUM200600CS <sup>1</sup>
	206	HUM206600CS <sup>2</sup>
8"	100	HUM100800CS <sup>1</sup>
	200	HUM200800CS <sup>1</sup>
	206	HUM206800CS <sup>2</sup>

<sup>1</sup> Includes nut

<sup>2</sup> Includes nut and O-ring

### Suction Service Fittings




HUSM500SW-1



HUSF500SW

Size	Figure	Description	Forged Steel Part #
5"	50	socket weld x suction male hammer union (includes O-ring, no nut)	HUSM500SW-1
		socket weld x suction female hammer union	HUSF500SW
5"	N/A	split nut, suction and discharge, black	HUS500RN

### Dixon Frac Fitting O-rings



Size	Figure	Nitrile Rubber Part #
3"	206	O238BU
4"	206	O347BU
6"	206	O440BU
8"	206	O447BU

### King Crimp® Style Short Frac Ferrules

#### Features

- Schedule 40 plated carbon steel to ASTM standards
- Consult Dixon for additional ferrule sizes



Hose I.D.	Hose O.D.		Ferrule Wall Thickness	Ferrule I.D.	Ferrule Overall Length	Carbon Steel Part #
	From	To				
8"	8-29/64"	8-36/64"	.120"	8.625"	4.25"	CFS800-1CS
	8-37/64"	8-44/64"	.120"	8.750"	4.25"	CFS800-2CS
	8-45/64"	8-52/64"	.120"	8.875"	4.25"	CFS800-3CS
	8-53/64"	8-60/64"	.120"	9.000"	4.25"	CFS800-4CS
	8-61/64"	9-4/64"	.120"	9.125"	4.25"	CFS800-5CS
	9-5/64"	9-12/64"	.120"	9.250"	4.25"	CFS800-6CS
	9-13/64"	9-20/64"	.120"	9.375"	4.25"	CFS800-7CS
	9-21/64"	9-28/64"	.120"	9.500"	4.25"	CFS800-8CS